

NAME

bignum - Transparent BigNumber support for Perl

SYNOPSIS

```
use bignum;

$x = 2 + 4.5, "\n"; # BigFloat 6.5
print 2 ** 512 * 0.1, "\n"; # really is what you think it is
print inf * inf, "\n"; # prints inf
print NaN * 3, "\n"; # prints NaN
```

DESCRIPTION

All operators (including basic math operations) are overloaded. Integer and floating-point constants are created as proper BigInts or BigFloats, respectively.

If you do

```
use bignum;
```

at the top of your script, `Math::BigFloat` and `Math::BigInt` will be loaded and any constant number will be converted to an object (`Math::BigFloat` for floats like 3.1415 and `Math::BigInt` for integers like 1234).

So, the following line:

```
$x = 1234;
```

creates actually a `Math::BigInt` and stores a reference to it in `$x`. This happens transparently and behind your back, so to speak.

You can see this with the following:

```
perl -Mbignum -le 'print ref(1234)'
```

Don't worry if it says `Math::BigInt::Lite`, `bignum` and friends will use `Lite` if it is installed since it is faster for some operations. It will be automatically upgraded to `BigInt` whenever necessary:

```
perl -Mbignum -le 'print ref(2**255)'
```

This also means it is a bad idea to check for some specific package, since the actual contents of `$x` might be something unexpected. Due to the transparent way of `bignum` `ref()` should not be necessary, anyway.

Since `Math::BigInt` and `BigFloat` also overload the normal math operations, the following line will still work:

```
perl -Mbignum -le 'print ref(1234+1234)'
```

Since numbers are actually objects, you can call all the usual methods from `BigInt/BigFloat` on them. This even works to some extent on expressions:

```
perl -Mbignum -le '$x = 1234; print $x->bdec()'
perl -Mbignum -le 'print 1234->binc()';
perl -Mbignum -le 'print 1234->binc->badd(6)';
perl -Mbignum -le 'print +(1234)->binc()'
```

(Note that print doesn't do what you expect if the expression starts with '(' hence the +)

You can even chain the operations together as usual:

```
perl -Mbignum -le 'print 1234->binc->badd(6);'  
1241
```

Under bignum (or bigint or bigrat), Perl will "upgrade" the numbers appropriately. This means that:

```
perl -Mbignum -le 'print 1234+4.5'  
1238.5
```

will work correctly. These mixed cases don't do always work when using Math::BigInt or Math::BigFloat alone, or at least not in the way normal Perl scalars work.

If you do want to work with large integers like under `use integer;`, try `use bigint::`

```
perl -Mbigint -le 'print 1234.5+4.5'  
1238
```

There is also `use bigrat;` which gives you big rationals:

```
perl -Mbigrat -le 'print 1234+4.1'  
12381/10
```

The entire upgrading/downgrading is still experimental and might not work as you expect or may even have bugs.

You might get errors like this:

```
Can't use an undefined value as an ARRAY reference at  
/usr/local/lib/perl5/5.8.0/Math/BigInt/Calc.pm line 864
```

This means somewhere a routine got a BigFloat/Lite but expected a BigInt (or vice versa) and the upgrade/downgrad path was missing. This is a bug, please report it so that we can fix it.

You might consider using just Math::BigInt or Math::BigFloat, since they allow you finer control over what get's done in which module/space. For instance, simple loop counters will be Math::BigInts under `use bignum;` and this is slower than keeping them as Perl scalars:

```
perl -Mbignum -le 'for ($i = 0; $i < 10; $i++) { print ref($i); }'
```

Please note the following does not work as expected (prints nothing), since overloading of '.' is not yet possible in Perl (as of v5.8.0):

```
perl -Mbignum -le 'for (1..2) { print ref($_); }'
```

OPTIONS

bignum recognizes some options that can be passed while loading it via `use`. The options can (currently) be either a single letter form, or the long form. The following options exist:

a or **accuracy**

This sets the accuracy for all math operations. The argument must be greater than or equal to zero. See Math::BigInt's `bround()` function for details.

```
perl -Mbignum=a,50 -le 'print sqrt(20)'
```

p or precision

This sets the precision for all math operations. The argument can be any integer. Negative values mean a fixed number of digits after the dot, while a positive value rounds to this digit left from the dot. 0 or 1 mean round to integer. See `Math::BigInt`'s `bround()` function for details.

```
perl -Mbignum=p,-50 -le 'print sqrt(20)'
```

t or trace

This enables a trace mode and is primarily for debugging `bignum` or `Math::BigInt`/`Math::BigFloat`.

l or lib

Load a different math lib, see *MATH LIBRARY*.

```
perl -Mbignum=l,GMP -e 'print 2 ** 512'
```

Currently there is no way to specify more than one library on the command line. This will be hopefully fixed soon ;)

v or version

This prints out the name and version of all modules used and then exits.

```
perl -Mbignum=v -e ''
```

METHODS

Beside `import()` and `AUTOLOAD()` there are only a few other methods.

Since all numbers are now objects, you can use all functions that are part of the `BigInt` or `BigFloat` API. It is wise to use only the `bxxx()` notation, and not the `fxxx()` notation, though. This makes it possible that the underlying object might morph into a different class than `BigFloat`.

CAVEAT

But a warning is in order. When using the following to make a copy of a number, only a shallow copy will be made.

```
$x = 9; $y = $x;
$x = $y = 7;
```

Using the copy or the original with overloaded math is okay, e.g. the following work:

```
$x = 9; $y = $x;
print $x + 1, " ", $y, "\n";      # prints 10 9
```

but calling any method that modifies the number directly will result in **both** the original and the copy being destroyed:

```
$x = 9; $y = $x;
print $x->badd(1), " ", $y, "\n";      # prints 10 10
```

```
$x = 9; $y = $x;
print $x->binc(1), " ", $y, "\n";      # prints 10 10
```

```
$x = 9; $y = $x;
print $x->bmul(2), " ", $y, "\n";      # prints 18 18
```

Using methods that do not modify, but test the contents works:

```
$x = 9; $y = $x;
$z = 9 if $x->is_zero();              # works fine
```

See the documentation about the copy constructor and `=` in overload, as well as the documentation in

BigInt for further details.

`inf()`

A shortcut to return `Math::BigInt->binf()`. Usefull because Perl does not always handle bareword `inf` properly.

`NaN()`

A shortcut to return `Math::BigInt->bnan()`. Usefull because Perl does not always handle bareword `NaN` properly.

`upgrade()`

Return the class that numbers are upgraded to, is in fact returning `$Math::BigInt::upgrade`.

MATH LIBRARY

Math with the numbers is done (by default) by a module called `Math::BigInt::Calc`. This is equivalent to saying:

```
use bignum lib => 'Calc';
```

You can change this by using:

```
use bignum lib => 'BitVect';
```

The following would first try to find `Math::BigInt::Foo`, then `Math::BigInt::Bar`, and when this also fails, revert to `Math::BigInt::Calc`:

```
use bignum lib => 'Foo,Math::BigInt::Bar';
```

Please see respective module documentation for further details.

INTERNAL FORMAT

The numbers are stored as objects, and their internals might change at anytime, especially between math operations. The objects also might belong to different classes, like `Math::BigInt`, or `Math::BigFloat`. Mixing them together, even with normal scalars is not extraordinary, but normal and expected.

You should not depend on the internal format, all accesses must go through accessor methods. E.g. looking at `$x->{sign}` is not a bright idea since there is no guaranty that the object in question has such a hashkey, nor is a hash underneath at all.

SIGN

The sign is either '+', '-', 'NaN', '+inf' or '-inf' and stored seperately. You can access it with the `sign()` method.

A sign of 'NaN' is used to represent the result when input arguments are not numbers or as a result of 0/0. '+inf' and '-inf' represent plus respectively minus infinity. You will get '+inf' when dividing a positive number by 0, and '-inf' when dividing any negative number by 0.

MODULES USED

`bignum` is just a thin wrapper around various modules of the `Math::BigInt` family. Think of it as the head of the family, who runs the shop, and orders the others to do the work.

The following modules are currently used by `bignum`:

```
Math::BigInt::Lite (for speed, and only if it is loadable)
Math::BigInt
Math::BigFloat
```

EXAMPLES

Some cool command line examples to impress the Python crowd ;)

```
perl -mbignum -le 'print sqrt(33)'
```

```
perl -Mbignum -le 'print 2*255'  
perl -Mbignum -le 'print 4.5+2*255'  
perl -Mbignum -le 'print 3/7 + 5/7 + 8/3'  
perl -Mbignum -le 'print 123->is_odd()'  
perl -Mbignum -le 'print log(2)'  
perl -Mbignum -le 'print 2 ** 0.5'  
perl -Mbignum=a,65 -le 'print 2 ** 0.2'
```

LICENSE

This program is free software; you may redistribute it and/or modify it under the same terms as Perl itself.

SEE ALSO

Especially *bigrat* as in `perl -Mbigrat -le 'print 1/3+1/4'`.

Math::BigFloat, *Math::BigInt*, *Math::BigRat* and *Math::Big* as well as *Math::BigInt::BitVect*, *Math::BigInt::Pari* and *Math::BigInt::GMP*.

AUTHORS

(C) by Tels <http://bloodgate.com/> in early 2002, 2003.